



HOAXHxD1000E0

22" Sonni STD - Open Frame Monitor Leds Backlight

Model	HOAXHxD1000E0	
Aspect Ratio	16:10	
Structure	Metal-cased Open Frame	
LCD Type	22" Active matrix TFT-LCD	
Active Area	473.76 (H) x 296.1(V)	
Monitor Dimensions	Width: Height: Depth:	
Max. Resolution	1680x3(RGB) x 1050	
Pixel pitch (mm)	0.282x 0.282	
Display Color	16.7M	
Brightness	800cd/m2	
Response Time(Typ.)	5ms	
Viewing Angle (Typ.at CR> 10)	Horizontal(left/right)	89°/89°
	Vertical(up/down)	89°/89°
Contrast Ratio(Typ.)	1300:1	
Video Input	VGA Input only	
Video Signal Input	Mini D-Sub 15-pin VGA	
Power Supply	Type: External brick Input: 100-240 VAC, 50-60 Hz Output: 12 volts	
Environment	Operating Temp.	0~50°C
	Storage Temp.	-20~60°C
	Operating RH:	5%~90%
	Storage RH:	8%~90%
MTBF	50.000 Hours	
LCD Back light Life(Typ.)	50.000 Hours	
OSD Control	Buttons	on/off, up, down, left, right
	Function	Contrast, brightness, Phase, Clock, Color,
Regular Warranty	1 year for controller; 1 year for	
Mount Interface	VESA standard 75mm and	
Certification	CE	

Options

•Our monitors are also available with different brightness (LED, viewing angle and operation & storage temperature range). Please ask for specific model.


•Optional Touch solutions:

•Zytronic Projected Capacitive TouchScreen ZybridX that allows you to have a front Sacrificial Glass, protecting your TouchScreen & Monitor, up to 10 mm thickness.

•Optional Transflective TT enhancement

Ordering Information

- HOAXHxD1000E0 Basic Product
- HOAXBxD1000E0 Basic Product with Transflective enhancement
- HOAXHxD1X00E0 Basic Product with TouchScreen ZybridX
- HOAXBxD1X00E0 Basic Product with Transflective enhancement and TouchScreen ZybridX



ZybridX TouchScreen & Controller (USB or RS232)

Front View



Back View

