



HOA303D10FDI0

32" Open Frame TFT/LCD Monitor – Full High Definition

Model	HOA303D10FDI0	
Aspect Ratio	16:9	
Structure	Metal-cased Open Frame	
LCD Type	31,55" Active matrix TFT-LCD	
Active Area	698.4 (H) x 392.85 (V)	
Monitor Dimensions	Width: Height: Depth:	
Max. Resolution	1,920 x 1080	
Pixel pitch (mm)	0.36375	
Display Color	16.7M	
Brightness	450cd/m2	
Response Time(Typ.)	8ms	
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	88°/88°
	Vertical(up/down)	88°/88°
Contrast Ratio(Typ.)	5000:1	
Video Input	VGA Input only	
Signal Input	H/V Separate Sync. (TTL)	
Video Signal Input	Mini D-Sub 15-pin VGA	
Environment	Operating Temp.	0~50°C
	Storage Temp.	-20~60°C
	Operating RH:	10%~90%
	Storage RH:	10%~90%
MTBF	60.000 Hours	
LCD Back light	60.000 Hours	
Weight (N.W/G.W)	TBC	
Power Consumption	TBC	
OSD Control	Buttons	on/off, up, down, left, Contrast, brightness, Phase, Clock, Color, Sharpness, etc...
	Function	
Regular Warranty	1 year for controller; 1 year for	

Options

- Our monitors are also available with different brightness (LED, viewing angle and operation & storage temperature range). Please ask for specific model.
- Optional Transflective TT enhancement

Ordering Information

- HOA303D10FDI0 Basic Product
- HOA3T3D10FDI0 Basic Product with Transflective enhancement

